



relationships **FORGED**
solutions **CAST**

U.V. International, LLC

360 Mt. Kemble Ave. Suite#2000, Morristown, NJ 07960

Ph: (973) 775 1660 | F: (973) 775 1680

uvnj@uvintl.com | www.uvintl.com

Ductile Iron Threaded X-Heavy Flanges for Ductile Iron Pipe

ANSI /AWWA C115/A21.15

Ref: DHF1021



Item Number	Nom. Pipe Size	Flange Outer Diameter	Bolt Circle	B.Hole Diameter	No. of Holes	Flange Thickness	Length through Hub	Weight lbs
DHF0003	3	8.25	6.62	0.88	8	1.12	1.56	12
DHF0004	4	10.00	7.88	0.88	8	1.25	1.75	20
DHF0006	6	12.50	10.62	0.88	12	1.44	1.94	32
DHF0008	8	15.00	13.00	1.00	12	1.62	2.19	61
DHF0010	10	17.50	15.25	1.12	16	1.86	2.38	77
DHF0012	12	20.50	17.75	1.25	16	2.00	2.56	125
DHF0014	14	23.00	20.25	1.25	20	2.12	2.69	160
DHF0016	16	25.50	22.50	1.38	20	2.25	2.88	230
DHF0018	18	28.00	24.75	1.38	24	2.38	3.00	265
DHF0020	20	30.50	27.00	1.38	24	2.50	3.31	270
DHF0024	24	36.00	32.00	1.62	24	2.75	3.75	310
DHF0030	30	43.00	39.25	2.00	28	3.00	4.75	480
DHF0036	36	50.00	46.00	2.25	32	3.38	5.37	706
DHF0042	42	57.00	52.75	2.25	36	3.69	5.62	959
DHF0048	48	65.00	60.75	2.25	40	4.00	6.00	1356

* Dimensions are in inches.

- ▶ Material: Ductile Iron ASTM A536 Grade 65-45-12
- ▶ Machined, Drilled in accordance with ANSI B16.1 - Class 250
- ▶ Threaded in accordance with ANSI/ASME B1.20.1(National Pipe Taper Threads)
- ▶ Rated for maximum working pressure of 250 psi
- ▶ Coating: Bare

**To order or for further details,
(800) 848-6884 | orders@uvintl.com**