



relationships **FORGED**
solutions **CAST**



U.V. International LLC

360 Mt. Kemble Ave. Suite#2000, Morristown, NJ 07960
Ph: (973) 775 1660 | F: (973) 775 1680
uvnj@uvintl.com | www.uvintl.com

Ductile Iron Threaded Mechanical Joint Adapter Bell

ANSI /AWWA C110/A21.10

Ref: DMA1021



| Item Number | Nom. Pipe Size | Flange Outer Diameter | Bolt Circle | B.Hole UNC tapped | No. of Holes | Flange Thickness | Overall Thickness | Diameter of Hub | Thread Length | Weight lbs |
|-------------|----------------|-----------------------|-------------|-------------------|--------------|------------------|-------------------|-----------------|---------------|------------|
| DMA0003 | 3 | 7.69 | 6.19 | 5/8 - 11 | 4 | 0.94 | 4.12 | 4.50 | 0.94 | 11 |
| DMA0004 | 4 | 9.12 | 7.50 | 3/4 - 10 | 4 | 1.00 | 4.25 | 5.32 | 1.00 | 13 |
| DMA0006 | 6 | 11.12 | 9.50 | 3/4 - 10 | 6 | 1.06 | 4.43 | 7.56 | 1.15 | 20 |
| DMA0008 | 8 | 13.37 | 11.75 | 3/4 - 10 | 6 | 1.12 | 4.75 | 9.73 | 1.38 | 28 |
| DMA0010 | 10 | 15.69 | 14.00 | 3/4 - 10 | 8 | 1.19 | 4.87 | 12.06 | 1.50 | 41 |
| DMA0012 | 12 | 17.94 | 16.25 | 3/4 - 10 | 8 | 1.25 | 5.12 | 14.16 | 1.75 | 53 |
| DMA0014 | 14 | 20.31 | 18.75 | 3/4 - 10 | 10 | 1.31 | 6.50 | 16.25 | 1.87 | 78 |
| DMA0016 | 16 | 22.56 | 21.00 | 3/4 - 10 | 12 | 1.38 | 6.75 | 18.44 | 2.06 | 97 |
| DMA0018 | 18 | 24.83 | 23.25 | 3/4 - 10 | 12 | 1.44 | 7.00 | 20.53 | 2.25 | 120 |
| DMA0020 | 20 | 27.08 | 25.50 | 3/4 - 10 | 14 | 1.50 | 7.25 | 22.63 | 2.43 | 146 |
| DMA0024 | 24 | 31.58 | 30.00 | 3/4 - 10 | 16 | 1.62 | 7.50 | 26.82 | 2.75 | 175 |
| DMA0030 | 30 | 39.12 | 36.88 | 1 - 8 | 20 | 1.81 | 9.13 | 32.75 | 3.38 | 283 |
| DMA0036 | 36 | 46.00 | 43.75 | 1 - 8 | 24 | 2.00 | 9.75 | 39.12 | 4.00 | 482 |
| DMA0042 | 42 | 53.12 | 50.62 | 1 1/4 - 7 | 28 | 2.00 | 10.50 | 46.00 | 4.00 | 642 |
| DMA0048 | 48 | 60.00 | 57.50 | 1 1/4 - 7 | 32 | 2.00 | 11.00 | 52.25 | 4.12 | 811 |

* Dimensions are in inches.

- ▶ Material: Ductile Iron ASTM A536 Grade 65-45-12
- ▶ MJ Bell in accordance with ANSI/AWWA C110/A21.10
- ▶ Flange Machined, Drilled and Faced
- ▶ Threaded in accordance with ANSI/ASME B1.20.1(National Pipe Taper Threads)
- ▶ Bolt Holes are UNC threaded for stud bolts.
- ▶ Coating: Bare

**To order or for further details,
(800) 848-6884 | orders@uvintl.com**