

Floats (Stainless Steel)

Ref: FBS-SPEC0422



Plain Float Ball



with Hex Spud Nut




with Round Nut



Internal Thread



Through Tube



Weighted



Mirror Finish

Application: Floats are ideal for use under pressure and at correspondingly high temperatures in water or corrosive liquids. Applications include: Air Valves, Boiler Feed Water Controls, Check Valves, Float Switches, Float Valves, Liquid level Controls, Oil Fields, Steam Traps, Sump Pumps, Tank Trucks, etc.

Materials:Stainless Steel 304 | Stainless Steel 316Styles:Plain, Spud Nut (Hex & Round), Internal threading, Through Tube, WeightedThickness:Gauges: 20, 18, 14Sizes:Dia: 2" - 12" | Spud size: 4" & 6": ¼", 8": 5/8"Finish:Plain

To order or for further details, please call (800) 848-6884 or email: orders@uvintl.com

Headquarters 360 Mount Kemble Ave. Suite 2000 Morristown, NJ 07960 Ph: (973) 775-1660 Fax: (973) 775-1680 Email: uvnj@uvintl.com

Distribution Centers

Hueytown, AL; Fontana, CA; West Sacramento, CA; Atlanta, GA; Hagerstown, MD; Minneapolis MN Dallas, TX; Houston, TX