

## Ductile Iron Threaded Flanges for Ductile Iron Pipe

### ANSI /AWWA C115/A21.15

Ref: DPF1021



Item Number	Nom. Pipe Size	Flange Outer Diameter	Bolt Circle	B.Hole Diameter	No. of Holes	Flange Thickness	Length through Hub	Weight (lbs)
DPF0003	3	7.5	6.00	0.75	4	0.75	1.69	7
DPF0004	4	9.0	7.50	0.75	8	0.94	1.81	12
DPF0006	6	11.0	9.50	0.88	8	1.00	2.00	17
DPF0008	8	13.5	11.75	0.88	8	1.12	2.24	25
DPF0010	10	16.0	14.25	1.00	12	1.19	2.44	34
DPF0012	12	19.0	17.00	1.00	12	1.25	2.56	51
DPF0014	14	21.0	18.75	1.12	12	1.38	2.64	69
DPF0016	16	23.5	21.25	1.12	16	1.44	2.64	87
DPF0018	18	25.0	22.75	1.25	16	1.56	2.76	89
DPF0020	20	27.5	25.00	1.25	20	1.69	2.87	110
DPF0024	24	32.0	29.50	1.38	20	1.88	3.11	153
DPF0030	30	38.8	36.00	1.38	28	2.24	4.00	212
DPF0036	36	46.0	42.75	1.62	32	2.52	5.00	324
DPF0042	42	53.0	49.50	1.62	36	2.76	5.12	534
DPF0048	48	59.5	56.00	1.62	44	2.87	5.50	646
DPF0054	54	66.3	62.75	2.00	44	3.00	7.16	760
DPF0060	60	73.0	69.25	2.00	52	3.12	7.16	1246
DPF0064	64	80.0	76.00	2.00	52	3.38	7.16	1788

\* Dimensions are in inches.

- ▶ Ductile Iron ASTM A536 (65-45-12)
- ▶ Bolt holes in accordance ANSI A21.1
- ▶ Machined, Drilled and Faced in accordance with ANSI B16.1 – Class 125
- ▶ Rated for a maximum working pressure 250 ps
- ▶ Threaded in accordance with ANSI /ASME B 1.20.1 (National Pipe Taper Threads)
- ▶ Coating : Bare

**To order or for further details,  
(800) 848-6884 | orders@uvintl.com**