



| Sr . N o. | Item Number | Description | Length | Pcs/Bundle | lbs./ft. | Price/ft. |
|-----------|---------------|--|--------|------------|----------|-----------|
| 1 | CSL/SWPG/1014 | Strut Channel Slotted 13/16" x 1-5/8" 14 gauge | 10' | 100 | 0.9 | \$2.30 |
| 2 | CSL/SWPG/1012 | Strut Channel Slotted 13/16" x 1-5/8" 12 gauge | 10' | 100 | 1.2 | \$2.60 |
| 3 | CSL/SWPG/2014 | Strut Channel Slotted 13/16" x 1-5/8" 14 gauge | 20' | 100 | 0.9 | \$2.50 |
| 4 | CSL/SWPG/2012 | Strut Channel Slotted 13/16" x 1-5/8" 12 gauge | 20' | 100 | 1.2 | \$2.90 |
| 5 | CSL/DPPG/1014 | Strut Channel Slotted 1-5/8" x 1-5/8" 14 gauge | 10' | 50 | 1.3 | \$3.30 |
| 6 | CSL/DPPG/1012 | Strut Channel Slotted 1-5/8" x 1-5/8" 12 gauge | 10' | 50 | 1.8 | \$3.80 |
| 7 | CSL/DPPG/2014 | Strut Channel Slotted 1-5/8" x 1-5/8" 14 gauge | 20' | 50 | 1.3 | \$3.60 |
| 8 | CSL/DPPG/2012 | Strut Channel Slotted 1-5/8" x 1-5/8" 12 gauge | 20' | 50 | 1.8 | \$4.20 |

Material: Carbon Steel ASTM A653 SS GR 33
Finish: Pre-galvanized:G90
Length: 10' & 20'
Thickness: 12 & 14 Gauge
Slots: Oval
Load Data: Loads are based on 33 ksi steel cold formed to 42 ksi
Safety Factor to Yield Strength is 1.67 for Beam Loads and 1.80 for Column Loads.

To order or for further details, please call (800) 848-6884 or email: orders@uvintl.com

Headquarters

360 Mount Kemble Ave. Suite 2000
Morristown, NJ 07960
Ph: (973) 775-1660 Fax: (973) 775-1680
Email: uvnj@uvintl.com

Distribution Centers

Hueytown, AL; Fontana, CA; West Sacramento, CA;
Atlanta, GA; Baltimore, MD; Minneapolis, MN;
Dallas, TX; Houston, TX; Kent WA

